morethansafety



# Test Equipment Kits

morethansafety



# LV Isolation Kit

# Test Equipment Kits LV Isolation Kit



KEWTECH



#### 5551188

#### 2 Pole LED Voltage Tester

#### **Key Benefits**

- Clear oversize luminous LEDs shine through voltage level
- Clear audible tone
- UK Specific GS38 Slender probe tips NO NEED to swap ends
- Bright torch light gives ample illumination
- Fits into recessed terminals such as RCBOs without unscrewing any caps
- Phase Rotation Bright green LEDs show left or right rotation.

Indicates actual voltage if no batteries fitted

Two pole testers that use batteries should indicate a live circuit if the batteries die or have not been inserted into the tester.

This is normally indicated by a single LED but this does not indicate the actual voltage present.

The KT1780 & KT1790 have a separate circuit so they operate with no batteries or dead batteries and still indicate the actual voltage present.

#### **Key Features**

- AC & DC Voltage tests up to 690V
- Clear Oversize luminous LED indication
- Soft to touch overmoulded rubber body
- Continuity Test
- Self diagnostic test
- Single Pole phase test
- Phase Rotation test
- Polarity indication
- Auto power on/off
- IP65 rating protects against Dust & Water ingress
- Designed to the new international safety standards IEC 61243-3 & IEC
- 61010-1
- Cat IV 600V

#### Included:

Built in test leads, Batteries
Instruction manual with Certificate of Conformity

Weights & Dimensions: Boxed Weight: 242g Boxed Dimensions: 300(H)mm x 40(H)mm x 70(D)mm

#### 5551215

#### **Proving Unit**

50-690 V proving unit with just two terminals to test AC and DC voltage detectors. Fast response and works with low impedance voltage testers. Ramps down through voltage levels. LED indication of functioning unit.

To ensure the safety of personnel working on electrical circuits BEST PRACTICE for the use of a proving unit before working on dead circuits.

Output voltage: Operating conditions: Dimensions: 180V in to 6.8  $\Omega$  , 720V – 820V in to 10M  $\Omega$ 

-10 to 40 C, 70% RH W65 x H120 x D45mm

### **Test Equipment Kits**

LV Isolation Kit





#### 5551377

#### Kitbag 3 for 2 Pole LED **Voltage Tester**

Carrying case for 2 Pole LED Voltage Tester. Branded zip kit bag with clear window. Case has 2 holes in proving unit storage section for testing without removal.

Dimensions: Length 31cm Width: 13cm Depth: 9cm

Material - cloth with carrying strap

#### 5551233

#### **Kewstick DUO (Non-Contact Voltage Detector**)

ITEM USED FOR INDICATION ONLY

Unique dual sensitive non-contact voltage detector - just press and hold the desensitising button and you can differentiate between live and earthed cables approximately 10mm apart.

#### **Key Benefits:**

- Dual sensitivity
- Heartbeat green LED indicates that the unit is on and working correctly
- Red LED indicates presence of voltage
- Audible tone also indicates the presence of voltage

#### Key Features:

Clearly detects 90 - 600 volts AC without metal contact Two colour LEDs - Green for correct working and Red for Voltage detection

Two tone buzzer, one for correct working and one for voltage detection

Pocket-size for handy use anywhere

Low power consumption circuits means long life batteries Cat IV rated

2 year unconditional guarantee (excluding batteries)

#### 5551617

#### Non Contact Proving Unit

Portable proving unit for use on / off site that instantly proves the function of non-contact voltage testers before and after use.

Simple to use, just press the button and tests. Belt clip for hands-free use. Visual LED indication of function. Robust and drop-proof from 1 metre. Comes installed with a 9V battery.



morethansafety.co.uk

### **Test Equipment Kits**

LV Isolation Kit





#### **Swift Spectacles Clear**

- Safety glasses with clear lenses are essential indoors.
- Bollé Safety clear lenses provide 90% light transmission.
- Compatible with the PLATINUM anti-fog coating.
- Tint base : Clear
- 90% Visible Light Trans

Designed to meet essential safety standards, SWIFT is an affordable safety eyewear that seamlessly combines design, comfort, and durability. Featuring our PLATINUM Lite anti-scratch and anti-fog coating, ensuring crystal-clear vision in all situations. Its well balanced frame provides daily comfort, while its flexible, contoured, and textured temples ensure optimal lateral protection, fit, and retention. As part of our Go Green range, SWIFT is crafted from 31% recycled polycarbonate, and is fully recyclable, with a mono-material design without any metal components. Choose the clear version with an eco-packaging option for greater sustainability.



#### **Arc Grip Glove**

The Arc Grip Glove provides a high level of protection against Arc Flash burns and cuts. The 13-gauge cut level D knitted liner is manufactured with a unique flame-resistant aramid yarn which provides increased dexterity and hand movement. The flame-resistant neoprene coated palm allows for excellent grip. Arc Flash level 2 (ATPV 9.5cal/cm2).

- Superb Arc-Flash Protection: Arc Rating (ATPV)= 9.5 cal/cm2
- ARC Grip glove provides a high level of protection against ARC flash burns and cuts
- Level D cut resistance
- 13 gauge liner constructed for durability and precise fitting
- Flame-resistant neoprene coated palm allows for excellent grip
- FR aramid thread for extra durability & protection
- CE certified
- Retail tag which aids presentation for retail sales
- ANSI cut level A4
- Sizes M XXL
- EN ISO 21420: 2020 Dexterity 5
- EN 388: 2016 + A1: 2018 4X42D
- EN 407: 2020 41XXXX
- ASTM F2675-13 Class 2
- ANSI/ISEA 105: 2016 CUT Level A5
- ANSI/ISEA 105: 2016 ABRASION Level 6



morethansafety



# Authorised Persons LV Kit



#### 5551188 2 Pole LED Voltage Tester

#### **Key Benefits**

- Clear oversize luminous LEDs shine through voltage level
- Clear audible tone
- UK Specific GS38 Slender probe tips NO NEED to swap ends
- Bright torch light gives ample illumination
- Fits into recessed terminals such as RCBOs
- without unscrewing any caps
- Phase Rotation Bright green LEDs show left or right rotation.

Indicates actual voltage if no batteries fitted

Two pole testers that use batteries should indicate a live circuit if the batteries die or have not been inserted into the tester.

This is normally indicated by a single LED but this does not indicate the actual voltage present.

The KT1780 & KT1790 have a separate circuit so they operate with no batteries or dead batteries and still indicate the actual voltage present.

#### **Key Features**

- AC & DC Voltage tests up to 690V
- Clear Oversize luminous LED indication
- Soft to touch overmoulded rubber body
- Continuity Test
- Self diagnostic test
- Single Pole phase test
- Phase Rotation test
- Polarity indication
- Auto power on/off
- IP65 rating protects against Dust & Water ingress
- Designed to the new international safety standards IEC 61243-3 & IEC
- 61010-1
- Cat IV 600V

Included: Built in test leads, Batteries Instruction manual with Certificate of Conformity

Weights & Dimensions: Boxed Weight: 242g Boxed Dimensions: 300(H)mm x 40(H)mm x 70(D)mm

#### 5551233

# Kewstick DUO (Non-Contact Voltage Detector)

#### ITEM USED FOR INDICATION ONLY

Unique dual sensitive non-contact voltage detector - just press and hold the desensitising button and you can differentiate between live and earthed cables approximately 10mm apart.

#### Key Benefits:

- Dual sensitivity
- Heartbeat green LED indicates that the unit is on and working correctly
- Red LED indicates presence of voltage
- Audible tone also indicates the presence of voltage

#### **Key Features:**

- Clearly detects 90 600 volts AC without metal contact
- LEDs Green for correct working and Red for Voltage detection
- Two tone buzzer, one for correct working + voltage detection
- Pocket-size for handy use anywhere
- Low power consumption circuits means long life batteries
- Cat iV rated







#### 1000A Ultra Slim Clamp Meter

Slim and lightweight 1000A clamp with 0.01A resolution

#### **Key Benefits**

- Slim, lightweight high capacity clamp meter from the world leaders in clamps.
- DMM functionality
- G7 test leads

#### **Key Features**

- 10mm Jaw thickness
- Tear drop jaw shape for easy access in to distribution boards
- 1000A Current measurement
- 0.01 A resolution
- AC Voltage measurement up to 600V
- ImV Resolution AC V
- DC Voltage measurement up to 600V
- 0.1mV Resolution DCV
- Resistance measurement
- Continuity buzzer
- Fuseless electronic protection on up continuity up to 600V
- Comes with popular G7 test leads
- Includes carry case with belt loop

Safety: IEC 61010-1 CAT.III 600V Pollution degree 2 (AC A), CAT.III 300V / CAT.II 600V Pollution degree 2 (AC/DC V)

IEC 61010-031, IEC 61010-2-032, IEC 61326 (EMC)

#### Included:

Test leads Carry pouch with belt loop Batteries Manual

#### 5551377

#### Kitbag 3 for 2 Pole LED Voltage Tester

Carrying case for 2 Pole LED Voltage Tester. Branded zip kit bag with clear window. Case has 2 holes in proving unit storage section for testing without removal

Dimensions: Length 31cm | Width: 13cm | Depth: 9cm Material: Cloth with carrying strap

#### 6202161

#### Branded Kitbag 4 (MFT Padded Bag)

Kitbag 4 (MFT Padded Bag) Width: 30cm Height: 18cm Depth: 18cm







#### 5551217

#### **Socket Tester**

Checks correct socket outlet wiring. Checks the quality of the earthing that is essential for safe installations. Checks for the polarity of the mains supply. Checks RCDs with measured current. Bright LEDs Easy to use - anything other than green needs checking out.



# TBC Arc Grip Glove

The Arc Grip Glove provides a high level of protection against Arc Flash burns and cuts. The 13-gauge cut level D knitted liner is manufactured with a unique flame-resistant aramid yarn which provides increased dexterity and hand movement. The flame-resistant neoprene coated palm allows for excellent grip. Arc Flash level 2 (ATPV 9.5cal/cm2).

#### **TBC**

#### **Swift Spectacles Clear**

Designed to meet essential safety standards, SWIFT is an affordable safety eyewear that seamlessly combines design, comfort, and durability.

- Safety glasses with clear lenses are essential indoors.
- Bollé Safety clear lenses provide 90% light transmission.
- Compatible with the PLATINUM anti-fog coating.
- Tint base: Clear
- 90% Visible Light Trans









#### 5551215 Proving Unit

50-690 V proving unit with just two terminals to test AC and DC voltage detectors. Fast response and works with low impedance voltage testers. Ramps down through voltage levels. LED indication of functioning unit.

To ensure the safety of personnel working on electrical circuits BEST PRACTICE for the use of a proving unit before working on dead circuits.

Output voltage: 180V in to 6.8  $\Omega$  , 720V - 820V in to 10M  $\Omega$  Operating conditions: -10 to 40 C, 70% RH W65 x H120 x D45mm

#### 5551617

#### **Non Contact Proving Unit**

Portable proving unit for use on / off site that instantlyproves the function of non-contact voltage testers before and after use.

Simple to use, just press the button and tests.

Belt clip for hands-free use.

Visual LED indication of function.

Robust and drop-proof from 1 metre.

Comes installed with a 9V battery.

Image: Non Contact Proving Unit plus Duo

#### 5551618

## Infrared Thermometer (Dual Channel)

An electrician specific infrared thermometer. Infrared thermometers take an average reading across a circular area, but the IR1200's two dot laster guidance clearly defines this area so you know exactly what you are measuring. Measures up to 1200°C.

- Second channel for contact temperature measurement for use with K type connectors (thermocouple included)
- Infrared temperature measurement up to 1200°C for non contact measurements.
- Ambient Temperature Function.
- Easy emissivity adjustment
- Thermocouple channel for contact measurements.
- Special two spot laser guidance gives unambiguous guidance of area being measured.
- Max, Min, Diff, Ave reading.
- Data hold
- High & Low alarm

**Accessories:** K type thermocouple, Battery, Operating Instructions